

## 3 ft DisplayPort™ to DVI Active Adapter Converter Cable – DP to DVI 2560x1600 – Black

StarTech ID: DP2DVIMM3BS



The DP2DVIMM3BS 3ft active DisplayPort to DVI converter cable lets you connect your DisplayPort-equipped desktop or laptop directly to a nearby DVI monitor or projector, saving the expense of additional adapters while eliminating the clutter of excess cable.

For guaranteed compatibility with virtually any DisplayPort output the active DisplayPort to DVI adapter supports multimode (DP++) as well as single-mode DisplayPort signals. Unlike passive adapters, this ensures the DP2DVIMM3BS can be used with graphics cards that are not capable of outputting multimode DP++ signals, such as ATI® Eyefinity cards.

Plus, because the converter cable supports video resolutions up to 2560x1600 you can convert a DisplayPort video source to DVI without sacrificing video quality.

The DP2DVIMM3BS is backed by a 2-year StarTech.com warranty and free lifetime technical support.

### Applications

- Use with single-mode DisplayPort video outputs that are not capable of outputting multimode DP++ signals, such as ATI® Eyefinity video cards
- Connect your DVI display device (monitor, projector) directly to a DisplayPort output device
- Ideal for using your DVI monitor as a secondary display

## Features

- Active DisplayPort to DVI conversion
- 1x Male DisplayPort connector, 1x Male DVI connector
- Supports resolutions up to 2560x1600 and HDTV resolutions up to 1080p
- Plug-and-play Installation

## Technical Specifications

Warranty	2 Years
Adapter Style	Cable Adapter
Audio	No
Chipset ID	PS171A
Converter Type	Active
Maximum Cable Length	3 ft [0.9 m]
Maximum Digital Resolutions	2560x1600 (Dual link)
Supported Resolutions	2560x1600 1920x1200 1920x1080
Wide Screen Supported	Yes
Connector A	1 - DisplayPort (20 pin) Male
Connector B	1 - DVI-D (25 pin) Male
Cable Length	3 ft [0.9 m]
Color	Black
Product Height	0.6 in [15 mm]
Product Length	36 in [915 mm]
Product Weight	2.8 oz [80.6 g]
Product Width	1.6 in [40 mm]
Humidity	40%-85%RH
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-10°C to 70°C (14°F to 158°F)
Shipping (Package) Weight	3.2 oz [91.6 g]
Included in Package	1 - Active DisplayPort to DVI Adapter

Certifications, Reports and Compatibility

