

USB Dual VGA over Cat5 KVM Console Extender - 650 ft / 200m

StarTech ID: SV565DUTPU



The SV565DUTPU USB Dual VGA KVM Console Extender over CAT5 UTP lets you Operate a Dual VGA PC or KVM switch up to 650ft (200 m) away, as if it was installed locally, at high-definition 1920x1200 resolution. PC connection cables are included with this product for a ready to use solution.

The dual VGA cat5 KVM extender supports easy to use hot-key and push button commands which allow you to switch between local and remote connected systems, while console connections at both ends of your setup provide easy access to all connected systems from either location. The hot-key commands also provide video adjustment controls for optimizing picture quality over varying distances. Extending over two standard Cat 5 (or better) cables gives you the ability to use existing infrastructure wiring to achieve remote access to your server or KVM switch.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Applications

- Ideal for controlling a PC in an area where fan or hard drive noise is unacceptable such as a television broadcast studio
- Control/Monitor a remote server from a harsh environment where the PC would not function properly due to heat/dust/etc. (factory, warehouse, mining, etc.)
- Can act as a thin client for power users controlling powerful rack mounted servers as their desktop machines
- Use one or more servers in a server room from a remote location within the same building or campus

Features

- Dual VGA KVM extender at 1920x1200 resolution
- Can be used with a single computer or connected to an existing KVM switch
- Extend up to 650 ft. (200 m) using 2 industry-standard UTP network cables
- KVM console connections available on both the local and remote end
- Supports most combo keyboard and mouse sets (including Wireless)
- Intuitive hot-key commands for fine-tuning video

Technical Specifications

Warranty	3 Years
Color	Black
Enclosure Type	Steel
Product Height	1.6 in [40 mm]
Product Length	6.1 in [155 mm]
Product Weight	18.9 oz [535 g]
Product Width	3.1 in [80 mm]
Audio	No
Cables Included	Yes
KVM Ports	2
Multi-Monitor	Yes
PC Interface	USB
PC Video Type	VGA
Rack-Mountable	No
IP Control	No
Max Transfer Distance	200 m (656 ft)
Maximum Analog Resolutions	1920x1200
Supported Resolutions	1920x1200 @ 650 ft (200m)
Console Interface(s)	2 - USB A (4 pin) Female
Console Interface(s)	2 - VGA (15 pin; High Density D-Sub) Female
Host Connectors	2 - VGA (15 pin; High Density D-Sub) Female
Other Interface(s)	2 - RJ-45 Female
OS Compatibility	OS independent; No software or drivers required
Note	Product weights/measurements and connector types indicate a single unit only (either Host or Remote)
Center Tip Polarity	Positive
Input Current	0.2A
Input Voltage	110 ~ 240 AC
Output Current	0.6A
Output Voltage	9 DC
Plug Type	M
Power Source	AC Adapter Included
Humidity	0~80% RH

Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-10°C to 60°C (14°F to 140°F)
Shipping (Package) Weight	5 lb [2.3 kg]
Included in Package	1 - Local Unit
Included in Package	1 - Remote Unit
Included in Package	2 - 6 ft 2-in-1 USB VGA KVM cables
Included in Package	2 - Packs Rubber Feet
Included in Package	1 - Universal Power Adapter (NA/EU/UK) and AU in Australia
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

