



RoHS



APCRBC141

★★★★★ 5.0 (2) Write a review

Genuine APC RBC(TM) are tested and certified for compatibility to restore UPS performance to the original specifications.

Includes: Battery recycling guide

Technical Specifications

Batteries & Runtime	
Battery type	Lead-acid battery
Battery mounting	Enclosed battery cartridge
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Physical	
Maximum Height	2.99inches (76MM, 7.6CM)
Maximum Width	8.27inches (210MM, 21.0CM)
Maximum Depth	15.75inches (400MM, 40.0CM)
Net Weight	25.79lbs. (11.7KG)
Shipping weight	28.99lbs. (13.15KG)
Shipping Height	7.99inches (203MM, 20.3CM)
Shipping Width	13.5inches (343MM, 34.3CM)
Shipping Depth	20.51inches (521MM, 52.1CM)
Color	Black
Units per Pallet	16.0
Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-15 - 45 °C

We use cookies to provide you with a better onsite experience. By continuing to browse the site you are agreeing to our use of cookies in accordance with our Cookie Policy.

Conformance		
Standard warranty	1 year repair or replace	
Custoin ship Offen Status		
Sustainable Offer Status	Compliant	
RoHS	Compliant Available in Documentation tab	
Proposition 65 Warning		
SIGN UP FOR EMAIL		
I'd like to receive news and commercial info from Sc Policy.	chneider Electric and its affiliates via electronic communication means such as email. For r	nore details, please read our Privac
Email		
I am a		~
	OK	
WHO WE ARE	CONNECT WITH US	
About APC	Press	
Investor Relations	APC Blog	
Careers	Schneider Electric Data Center Blog	
Sustainability	Contact Us	
FIND A RESELLER		
Zip/Postal Code		Find
CATALOG KEYCODE		
Enter Key Code		Go
Terms & Conditions		
Data Privacy and Cookie Policy		
2021, APC by Schneider Electric		

We use cookies to provide you with a better onsite experience. By continuing to browse the site you are agreeing to our use of cookies in accordance with our Cookie Policy.