



APCRBC142

RoHS

Genuine APC RBC(TM) are tested and certified for compatibility to restore UPS performance to the original specifications.

Includes: All required connectors, Battery recycling guide, Installation guide, Reusable packaging

Technical Specifications

Output

Battery Output Voltage	24
------------------------	----

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Stand alone battery stack
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery blocks per string	2

Physical

Maximum Height	108MM, 10.8CM
Maximum Width	132MM, 13.2CM
Maximum Depth	150MM, 15.0CM
Net Weight	6.01KG
Shipping weight	7.01KG
Shipping Height	203MM, 20.3CM
Shipping Width	168MM, 16.8CM
Shipping Depth	224MM, 22.4CM
Units per Pallet	75.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters

Back to top



Conformance

Standard warranty	1 year repair or replace
--------------------------	--------------------------

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Proposition 65 Warning	Available in Documentation tab

Back to top

