

AP7155B




Metered rack Power Distribution Units (PDUs) provide real-time remote monitoring of connected loads. User-defined alarms warn of potential circuit overloads before ...

Includes: Documentation CD, Rack mounting brackets, RS-232 configuration cable



Technical Specifications

Output

Always on Outlets	1
Overload Protection	No
Cord Length	0.9meters
Maximum Total Current Draw	32

Input

Input frequency	50/60 Hz
Acceptable Input Voltage	220 - 250VAC
Number of Power Cords	1
Load Capacity	7360VA
Maximum Input Current	32A
Maximum Line Current	32A

Physical

Maximum Height	44MM, 4.4CM
Maximum Width	178MM, 17.8CM
Maximum Depth	140MM, 14.0CM
Net Weight	2.25KG
Shipping weight	2.89KG
Shipping Height	246MM, 24.6CM
Shipping Width	330MM, 33.0CM
Shipping Depth	185MM, 18.5CM

Environmental

Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters

Storage Temperature	-25 - 65 °C
Storage Elevation	0 - 15240meters

Conformance

Approvals	AS/NZS 3548 (C-Tick) class A, C-Tick, CE, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IEC 61000-3-2, IEC 61000-3-3, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
-------------	-----------

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our Privacy Policy.

Sign up

WHO WE ARE

- About APC
- Investor Relations
- Careers
- Sustainability

CONNECT WITH US

- Press
- APC Blog
- Schneider Electric Data Center Blog
- Contact Us

FIND A RESELLER

 Find

CATALOG KEYCODE

 Go


Terms & Conditions

Data Privacy and Cookie Policy

2020, APC by Schneider Electric