



APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack Marine

SRT192RMBPM



\$1,475.00*

Call for More Information 800-800-4272

- High availability, ruggedized power protection for shipboard and other transportation applications.
- Includes: Installation guide, Warranty card

Output	
Battery Output Voltage	192V
Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Stand alone battery stack
Expected Battery Life (years)	3 - 5
RBC Quantity	2
Battery blocks per string	
Physical	
Maximum Height	5.1inches (130MM, 13.0CM)
Maximum Width	17.0inches (432MM, 43.2CM)
Maximum Depth	26.88inches (682MM, 68.27CM)
Rack Height	3U
Net Weight	200.2lbs. (91.0KG)
Shipping weight	232.1lbs. (105.5KG)
Shipping Height	16.54inches (420MM, 42.0CM)
Shipping Width	23.63inches (600MM, 60.0CM)
Shipping Depth	39.38inches (1000MM, 100.0CM)
Color	Black
Units per Pallet	1.0

*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack Marine | SRT192RMBPM | Downloaded on 07/09/2019 (EST)



Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (no %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (no %
Storage Elevation	0-50000ft (0-15000meters)
Conformance	
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Other Environmental Compliance	China RoHS

*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.