



APC 5kVA and 6kVA Marine Filter

SRT6M

Call for More Information 1-800-880-877

- High availability, ruggedized power protection for shipboard and other transportation applications.
- Includes: Installation guide, Mounting hardware, User Manual

Output	
Nominal Output Voltage	200V, 208V, 220V, 230V, 240V
Other Output Voltages	208, 220, 230, 240
Maximum Total Current Draw	50
Output Connections	(1) Hard Wire 3-wire (H N + G) (Battery Backup)

Input	
Nominal Input Voltage	200V, 208V, 220V, 230V, 240V
Input frequency	45 - 65 Hz
Input Connections	Hard Wire 3-wire
Acceptable Input Voltage	100-240VAC
Load Capacity	6000VA
Maximum Input Current	50A
Maximum Line Current	50A
Regulatory Derated Input Current (North America)	50A

Physical	
Maximum Height	44MM, 4.4CM
Maximum Width	483MM, 48.3CM
Maximum Depth	330MM, 33.0CM
Rack Height	1U
Net Weight	6.73KG
Shipping weight	8.27KG
Shipping Height	76MM, 7.6CM
Shipping Width	559MM, 55.9CM

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC 5kVA and 6kVA Marine Filter | SRT6M | Downloaded on 03/29/2019 (EST)

Physical	
Shipping Depth	406MM, 40.6CM
Color	Black
Units per Pallet	60.0

Environmental	
Operating Temperature	0 - 55 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-25 - 75 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters

Conformance	
Approvals	DNV
Standard warranty	2 year (manufacturer's defect)

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.