

# ViewSonic® LED DISPLAY **VG2448**

---

## Key Features



## Product Description

ViewSonic VG2448 is a 24" (23.8" viewable) 1080p monitor with productivity enhancing features including IPS technology and an advanced ergonomic design for the modern day office. Utilising SuperClear® IPS technology and 1080p resolution, VG2448 delivers a crisp, clear image from any viewing angle. An advanced ergonomic design offers the widest range of customisable adjustments currently available to provide maximum comfort, including dual direction pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2448 uses environmentally friendly packaging and offers quick and easy out-of-the-box set-up via the Quick Release stand. The cloud client mountable stand coupled with cable management design features, makes VG2448 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.0 inputs.

---

**Visit Us** ■ [www.viewsonic.com](http://www.viewsonic.com)

**LCD PANEL**

Monitor Size:	24"W (23.8" Viewable)
Panel Technology:	SuperClear® IPS TFT LCD
Resolution:	FHD 1920 x 1080
Display Area:	527.04 mm (H) x 296.46 mm (V)
Aspect Ratio:	16:9
Brightness:	250 cd/m <sup>2</sup> (Typ)
Contrast Ratio:	1000:1 (Typ)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angle:	178 / 178 (Typ)
Response Time:	5ms (GtG)
Pixel Pitch:	0.2745 (H)mm x 0.2745(V)mm

**INPUT SIGNAL**

Frequency:	Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz
Sync:	Separate Sync / Composite Sync / Sync on Green

**COMPATIBILITY**

PC:	Windows 7, Windows 8, Windows 10 certified
Mac®:	Power Mac tested

**CONNECTOR**

Digital:	HDMI x 1 (v1.4 compatible) DisplayPort x 1 (v1.2 compatible)
Analog:	VGA x 1

**SPEAKERS**

2W x 2

**USB**Up Stream:Type B x 1  
Down Stream:Type A x 4**POWER**

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	21W
Optimize:	18W
Conserve:	15W

**ERGONOMICS**

Tilt:	40 ~ -5 degrees
Swivel:	120 degrees
Pivot:	180 degrees
Height Adjustment:	0 ~ 130mm

**WALL MOUNT**

VESA®:	100mm x 100mm
--------	---------------

**OPERATING CONDITIONS**

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

**DIMENSIONS (W X H X D) (MM)**

Physical with stand (mm):	549 mm (W) x 517 mm (H) x 202 mm (D)
Physical without stand (mm):	549 mm (W) x 326 mm (H) x 50 mm (D)
Packaging (mm):	604 mm (W) x 385 mm (H) x 210 mm (D)

**WEIGHT**

Net with stand (kg):	5.82kg
Net without stand (kg):	3.44kg
Gross (kg):	8.71 kg

**REGULATIONS**

FCC-B, Energy Star 7.0, EPEAT Gold, CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, REACH SVHC List & DoC, WEEE, TCO 7.0, EAC / CU, UkrSEPRO,RCM, GEMS(MEPS), VCCI, PSE

**PACKAGE CONTENTS**

LCD Display  
Power Cable  
DisplayPort Cable  
USB3.0 Upstream Cable  
Quick Start Guide

\*Actual content may differ from market to market