

Universal DC Power Adapter for Industrial USB Hubs - 20V, 3.25A

Product ID: ITB20D3250



This universal DC power adapter has been designed as an alternative, back up or replacement power supply for StarTech.com's line of industrial USB hubs.

Compatible USB 3.0 Hubs

10-Port Industrial USB 3.0 Hub with External Power Adapter - ESD & 350W Surge Protection ([HB30A10AME](#))

10-Port Industrial USB 3.0 Hub with ESD & 350W Surge Protection ([ST1030USBM](#))

7-Port Industrial USB 3.0 Hub with External Power Adapter - ESD & 350W Surge Protection ([HB30A7AME](#))

7-Port Industrial USB 3.0 Hub with ESD & 350W Surge Protection ([ST7300USBME](#))

4-Port Industrial USB 3.0 Hub with ESD Protection ([ST4300USBM](#))

Compatible USB 2.0 Hubs:

7-Port Industrial USB 2.0 Hub ESD Protection & 350W Surge Protection ([HB20A7AME](#))

7-Port Industrial USB 2.0 Hub with ESD & 350W Surge Protection ([ST7200USBM](#))

4-Port Industrial USB 2.0 Hub with ESD Protection & 350W Surge Protection ([HB20A4AME](#))

4-Port Industrial USB 2.0 Hub with ESD Protection ([ST4200USBM](#))

The external terminal power adapter can also be used with any other devices that can support 20V power supply including a variety of StarTech.com Ethernet Switches and Serial Adapters.

The ITB20D3250 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Features

- Terminal block power adapter has been designed for StarTech.com industrial products
- Use as an alternative power source, replacement, or back-up power supply when sufficient bus-power is unavailable
- Includes regional plug attachments for NA/JP, EU, UK & ANZ
- Includes an attached two conductor terminal block
- Includes an additional three conductor terminal block

Power	Warranty	1 Year
	Input Current	1.4A Max.
	Input Voltage	110V-240V AC
	Output Current	3.25A
	Output Voltage	20V DC
	Plug Type	Terminal Block (2 Wire) Terminal Block (3 Wire)
	Power Consumption (In Watts)	65W
Environmental	Humidity	20% ~ 80% RH
	Operating Temperature	+ 0°C ~ + 40°C
	Storage Temperature	- 20 °C ~ + 80°C
Physical Characteristics	Product Height	1.5 in [3.8 cm]
	Product Length	12.6 in [31.9 cm]
	Product Width	2.1 in [5.3 cm]
	Weight of Product	0.7 lb [0.3 kg]
Packaging Information	Package Height	55.000
	Package Length	166.000
	Package Width	242.000
	Shipping (Package) Weight	810.000
What's in the Box	Included in Package	1 - Universal 65W Power Adapter
		4 - Power Cords (NA/JP, EU, UK, ANZ)
		1 - Two Conductor Terminal Block Connector (Attached)
		1 - Three Conductor Terminal Block Connector
		1 - Quick Start Guide

Product appearance and specifications are subject to change without notice.