



APCRBC159

Genuine APC RBC(TM) are tested and certified for compatibility to restore UPS performance to the original specifications.

Includes: All required connectors, Battery recycling guide, Metallic battery tray or enclosure

Technical Specifications

Input

Number of Power Cords	1
-----------------------	---

Batteries & Runtime

Battery type	Lead-acid battery
Battery mounting	Enclosed battery cartridge
Expected Battery Life (years)	3 - 5
RBC Quantity	1

Physical

Maximum Height	83MM, 8.3CM
Maximum Width	216MM, 21.6CM
Maximum Depth	343MM, 34.3CM
Net Weight	11.96KG
Shipping weight	12.6KG
Shipping Height	152MM, 15.2CM
Shipping Width	368MM, 36.8CM
Shipping Depth	495MM, 49.5CM
Color	Black
Units per Pallet	20.0

Environmental

Operating Temperature	0 - 40 °C
-----------------------	-----------

We use cookies to provide you with a better onsite experience. By continuing to browse the site you are agreeing to our use of cookies in accordance with our [Cookie Policy](#).

OK

Storage Temperature	-15 - 45 °C
Storage Elevation	0 - 15240meters
Conformance	
Standard warranty	1 year repair or replace

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

Sign up

WHO WE ARE

- About APC
- Investor Relations
- Careers
- Sustainability

CONNECT WITH US

- Press
- APC Blog
- Schneider Electric Data Centre Blog
- Contact Us

FIND A RESELLER

CATALOG KEYCODE

 

[Terms & Conditions](#)
[Data Privacy and Cookie Policy](#)
2021, APC by Schneider Electric

We use cookies to provide you with a better onsite experience. By continuing to browse the site you are agreeing to our use of cookies in accordance with our [Cookie Policy](#).

OK