

ASUS uses cookies and similar technologies to perform essential online functions, analyze online activities, provide advertising services and other functions. For detailed information, please visit "[Cookies and similar technologies](#)".

[Cookie Settings](#)[Accept Cookies](#)[Products](#)[What's Hot](#)[Commercial](#)[Service](#)

P11C-C/4L

Processor / System Bus¹ x Socket LGA1151

Intel® Xeon® processor E-2100 family

Intel® Core™ i3 processors

Intel® Pentium™ processors

Intel® Celeron™ processors

Core Logic Intel® C242 Chipset

Memory Total Slots : 4 (2-channel)

Capacity : Maximum up to 64GB UDIMM

Memory Type :

DDR4 2666/2400 UDIMM non ECC and with ECC

Memory Size :

16GB, 8GB, 4GB

* Refer to support page for more information

Expansion Slots Total Slot : 3

Slot Location 1 : PCI 32bit/33MHz

Slot Location 5 : PCI-E x8

Slot Location 6 : PCI-E x16

Slot Location 7 : MIO Slot for Audio card

Follow SSI Location#

Form Factor ATX (12"x9.6", 305mm x 244mm)

ASUS Features FAN speed control
Rack Ready (Rack and Pedestal dual use)
ASUS Control Center

Storage SATA Controller :

Intel® C242 Chipset
6 x SATA3 6Gb/s ports
2 x M.2 connector(2242/2260/2280/22110) both SATA & PCIe mode *1
Intel® Rapid Storage Technology Enterprise(RSTe) (For Linux/Windows)
(Support Software RAID 0, 1, 5, 10)

SAS Controller :

ASUS PIKE II 3008-8i 8-port SAS 12G RAID card(Optional)
ASUS PIKE II 3108-8i 8-port SAS 12G HW RAID card(Optional)

Networking 4 x Intel® I210AT + 1 x Mgmt LAN

Graphic Aspeed AST2500 with 32MB VRAM

On Board I/O 1 x TPM header

1 x PSU Power Connector (24-pin ATX power connector + 8-pin ATX 12V power connector)
1 x COM port
1 x USB 3.0 pin header
1 x USB 2.0 pin header
1 x USB connector*2
6 x Fan Header , 4pin
1 x SMBus
1 x Chassis Intruder
4 x Front LAN LED
2 x Serial Port Header
1 x VGA Header
2 x M.2 Connector
1 x Onboard header for optional management card

Back I/O Ports 1 x External Serial Port

2 x USB 3.1 Gen 2
2 x USB 3.1 Gen 1
1 x VGA Port
4 x GbE LAN + 1 x Mgmt LAN

Management Solution ASUS Control Center
Optional ASMB9-iKVM for KVM-over-Internet

Weight Gift Box (1-in-1)

Net Weight : 0.76 KG

Gross Weight : 1.3 KG

Bulk Pack (10-in-1)

Net Weight : 6.9 KG

Gross Weight : 9.5 KG

Environment Operation temperature: 10°C ~ 35°C

Non operation temperature: -40°C ~ 70°C

Non operation humidity: 20% ~ 90% (Non condensing)

Accessories Gift Box (1-in-1)

2 x Support CD

1 x I/O shield

6 x SATA 6G cables

1 x Plate for LGA1151

Bulk Pack (10-in-1)

2 x Support CD

1 x I/O shield

1 x Plate for LGA1151

Monitoring CPU Temperature

Fan RPM

Note*1 2 x M.2 (NGFF 22110/2280/2260/2242, support PCIE or SATA signal, gray SATA port will disable when M.2 is SATA signal)

*2 1 x USB 3.0 connector (Type A USB socket)

- Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products.
- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- Specifications and features vary by model, and all images are illustrative. Please refer to specification pages for full details.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.
- The information contained is general testing result for reference. Please consult local sales representative for more information on specific supported CPU list on each system.

Want More?

Who We Are

Need Help?

Community

Global / English

[Terms of Use Notice](#) | [Privacy Policy](#) | ©ASUSTeK Computer Inc. All rights reserved.