

PRIME B550M-K

CPU

Build in AMD AM4 Socket 3rd Gen AMD Ryzen™ Processors *

* Refer to www.asus.com for CPU support list

Chipset

AMD B550

Memory

3rd Gen AMD Ryzen™ Processors

4 x DIMM, Max. 128GB, DDR4

4600(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3333(O.C.)/3200/3000/2800/2666/2400/2133 MHz Un-buffered Memory *

Next Generation AMD Ryzen PRO Processors

4 x DIMM, Max. 128GB, DDR4

4800(O.C.)/4600(O.C.)/4466(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3333(O.C.)/3200/3000/2800/2666/2400/2133 MHz Un-buffered Memory *

Dual Channel Memory Architecture

ECC Memory (ECC mode) support varies by CPU.

* Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists).

Graphic

1 x D-Sub

1 x DVI-D

1 x HDMI 2.1(4K@60HZ)

Expansion Slots

3rd Gen AMD Ryzen™ Processors

1 x PCIe 4.0 x16 (x16 mode)

AMD B550 Chipset

2 x PCIe 3.0 x1

Storage

Total supports 2 x M.2 slots and 4 x SATA 6Gb/s ports

3rd Gen AMD Ryzen™ Processors :

1 x M.2 Socket 3, with M Key, Type 2242/2260/2280/22110(PCIE 4.0 x4 and SATA modes) storage devices support

AMD B550 Chipset :

1 x M.2 Socket 3, with M Key, Type 2242/2260/2280 (PCIE 3.0 x4 and SATA

modes) storage devices support
4 x SATA 6Gb/s port(s),
Support Raid 0, 1, 10

LAN Realtek RTL8111H 1Gb Ethernet

Audio Realtek ALC887 7.1 Surround Sound High Definition Audio CODEC
- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback

Audio Feature :

- LED-illuminated design
 - Audio Shielding
 - Dedicated audio PCB layers
 - Premium Japanese audio capacitors
- * Choose the chassis with HD audio module in front panel to support 8-channel audio output.

USB Ports **Rear USB Port** (Total 6)

2 x USB 3.2 Gen 2 port(s)(2 x Type-A)
4 x USB 3.2 Gen 1 port(s)(4 x Type-A)

Front USB Port (Total 6)

2 x USB 3.2 Gen 1 port(s)(2 x Type-A)
4 x USB 2.0 port(s)(4 x Type-A)

Software Features ASUS Exclusive Software

Armoury Crate

AI Suite 3

- Performance And Power Saving Utility

TurboV EVO

EPU

Digi+ VRM

Fan Xpert 2+

- EZ update

ASUS CPU-Z

AI Charger

DAEMON Tools

Norton Anti-virus software (Free Trial for 60 days)

WinRAR

UEFI BIOS

ASUS EZ DIY

- ASUS CrashFree BIOS 3
- ASUS EZ Flash 3
- ASUS UEFI BIOS EZ Mode

ASUS Special Features ASUS 5X PROTECTION III

- ASUS DIGI+ VRM
- ASUS LANGuard

- ASUS Overvoltage Protection
- ASUS SafeSlot Core
- ASUS Stainless-Steel Back I/O

ASUS Q-Design

- ASUS Q-DIMM
- ASUS Q-Slot

ASUS Thermal Solution

- Aluminum heatsink design

ASUS Lighting Control

Back I/O Ports

- 1 x PS/2 keyboard/mouse combo port(s)
- 1 x DVI-D
- 1 x D-Sub
- 1 x HDMI
- 1 x LAN (RJ45) port(s)
- 2 x USB 3.2 Gen 2 (teal blue) (2 x Type-A)
- 4 x USB 3.2 Gen 1 (blue) Type-A
- 3 x Audio jack(s)

Internal I/O Ports

- 1 x CPU Fan connector(s)
- 2 x Chassis Fan connector(s)
- 1 x USB 3.2 Gen 1 (up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s)
- 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s)
- 1 x M.2 Socket 3 with M key, type 2242/2260/2280/22110 storage devices support(SATA & PCIe 4.0 x4 mode)
- 1 x M.2 Socket 3 with M key, type 2242/2260/2280 storage devices support (SATA & PCIe 3.0 x 4 mode)
- 1 x SPI TPM header
- 4 x SATA 6Gb/s connector(s)
- 1 x S/PDIF out header(s)
- 1 x 24-pin EATX Power connector(s)
- 1 x 8-pin EATX 12V Power connectors
- 1 x Front panel audio connector(s) (AAFP)
- 1 x Clear CMOS jumper(s)
- 1 x System panel connector
- 1 x COM port header
- 1 x Speaker connector

Accessories

- User's manual
- I/O Shield
- 2 x SATA 6Gb/s cable(s)
- 1 x Supporting DVD
- 1 x M.2 SSD screw package(s)

BIOS

256 Mb Flash ROM, UEFI AMI BIOS

ManageabilityWOL by PXE

Operating SystemWindows® 10 64-bit

Form FactorATX Form Factor
9.6 inch x 9.6 inch (24.4 cm x 24.4 cm)



- Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products.
- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- Specifications and features vary by model, and all images are illustrative. Please refer to specification pages for full details.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.
- Specifications and features vary by model, and all images are illustrative. Please refer specification pages for full details.
- *Precise specifications and features vary by model . Please refer to the specification page
- The product (electrical , electronic equipment, Mercury-containing button cell battery) should not be placed in municipal waste. Check local regulations for disposal of electronic products.
- The use of trademark symbol (TM, ®) appears on this website means that the word text, trademarks, logos or slogans, is being used as trademark under common laws protection and/or registered as Trademark in U.S. and/or other country/region.

Want More?

Who We Are

Need Help?

Community

Global / English

[Privacy Policy](#) | [Terms of Use Notice](#) | ©ASUSTeK Computer Inc. All rights reserved.