

Eaton 3S UPS

600/850 VA



Eaton 3S provides power and surge protection for desktop computers, wireless networks, gaming consoles, and other critical equipment in your home or business.

Full protection

- Eaton 3S supplies battery backup power during outage and advanced surge protection to prevent damage from lightning strikes or accidental grid surge.
- If power outage lasts longer than expected, Eaton software will gracefully shutdown your computer without losing any data
- Eaton 3S also integrates RJ11/xDSL connection to protect Internet gateways from perturbation through data line (850VA models).

Complete protection for:

- Computers, peripherals and multimedia
- TV, video and Hi-Fi equipment: Home cinema, NAS, digital decoders, etc...
- Internet gateways
- Gaming console
- Broadband modems (Internet and TV) & IP telephony
- Household goods, etc...

Modern usage and easy integration

- Compact and appealing design with glossy finish will perfectly fit in any modern residential or office environment.
- Eaton 3S 850VA offer two 2A USB ports to charge any mobile devices (mobile phone, tablet, etc..).
- To facilitate installation, wall mounting system is implemented on all models.



Peace of mind

- Surge protection circuits are compliant with IEC 61643-11 international standard
- 10A circuit breaker protects your equipment from overload (all models).

EATON

Powering Business Worldwide

Eaton 3S UPS

- 1 4 AU outlets with surge protection
- 2 4 AU outlets with battery backup & surge protection
- 3 On / Off button
- 4 LED interface
- 5 USB communication
- 6 Replaceable battery
- 7 Reset button (circuit breaker)
- 8 Wall-mounting system



Eaton 3S 600 AU



Eaton 3S 850 AU

- 1 4 AU outlets with surge protection
- 2 4 AU outlets with battery backup & surge protection
- 3 USB charge
- 4 On / Off button
- 5 LED interface
- 6 USB communication
- 7 Phone/xDSL line protection
- 8 Replaceable battery
- 9 Reset button (circuit breaker)
- 10 Wall-mounting system

Technical specifications

	Eaton 3S 600	Eaton 3S 850
Rating (VA/W)	600VA/360W	850VA/510W
Connection		
Output connection	4 outlets with battery backup and surge protection + 4 outlets with surge protection	
Electrical characteristics		
Nominal input voltage	220 - 240 V	
Input voltage range	Up to 168-295 V (adjustable)	
Output voltage	240V (adjustable to 220V/230V/240V)	
Input frequency range	50 / 60 Hz (46 - 65 Hz working range)	
Input protection	10A resettable circuit breaker	
Battery		
Battery type	Compact, sealed lead acid battery (replaceable)	
Battery test	Yes	
Cold start (no mains power)	Yes	
Deep-discharge protection	Yes	
Battery replacement indicator	LED	
Desktop PC*	16 min	20 min
Gaming PC / Workstation*	6 min	9 min
Features		
Communication	USB port (HID-compliant) for automatic integration with most common operating systems (Windows & Mac OS)	
USB charge	-	2 USB ports (2A max)
Phone/xDSL line protection	-	Yes
Operating conditions, Standards and Approvals		
Operating temperature	0 to 40° C	
Operationg elevation	0 to 3000m	
Compliances	IEC 62040-1; IEC 62040-2 C2; IEC 62040-3; IEC 62040-4; IEC 61643-11	
Conformity	CE / RCM	
Dimensions W x H x D / Weight		
UPS Dimensions (mm)	325x86x140	335x86x170
UPS Weight (kg)	3.2	4.3
Customer service & support		

* Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.